

Herculan ConstaBoost™

## Emergency Shower/Eyewash Water Supply

- Complete Storage & Delivery System • Use where no potable water is available • Use when existing supply is undersized • Use for work sites requiring emergency shower

SSPB210+210WSV-100-20EF when water source is available

SSPB210+210LFV-100-20 no water source available



- Complete, fully automatic Turn Key System
- Module components fit through 24" doors
- Built in pump requires a 240 Volt 20amp circuit
- -EF models have electric solenoid valve controlled fill with manual activation feature and require an additional 120 Volt 1 amp circuit
- Low water cut off protects delivery pump
- Quietly delivers 20 gpm @ 50 PSI
- Use where you need a shower/eyewash but do not have a water source to supply it
- Use on job sites
- Use when water supply piping undersized or source inadequate
- When -EF models are used with low yield well adjustable fill rate controls over pumping of well
- Tanks made of HDPE resin meeting FDA regulation 21 CFR 177.1520 © 3.1 & 3.2
- Level controls, piping, fittings NSF 61 compliant
- Pump contains no brass
- Recirculation line allows testing without water loss & helps with water treatment and bringing water to proper initial temp.
- Chlorine test kit included
- Operation & maintenance manual

System shown is at Kooltronic Inc. in New Jersey. Their paint line and required emergency shower are on the other side of the wall. By installing this system they avoided upsizing several hundred feet of overhead piping and installing a heater to bring the water to the required 60 degrees F. Plant engineer supplied bumper guard.

Sold By:

With our Patented PumpChamber™  
Herculan ConstaBoost™ and PumpChamber™  
are trademarks of  
Reid Plumbing Products, LLC  
371 Route 31N, Hopewell, NJ 08525  
800-211-8070 Outside the US 609-466-4347  
[www.wellmanager.com](http://www.wellmanager.com)

***"The water you need  
The performance you want"***



Auto fill switch on -EF models

Pressure Pump Switch



Gage shows system pressure. System provides 20 gpm @ 50 PSI

Tank fill on -EF systems. Turned off after tank is filled to keep water temp at 60+ degrees F. Fill shuts off automatically when tanks are full

1" FIP connection for pressure discharge to shower. Not shown is bypass on other side of wall

Valve allows circulating water from one tank to the other. Allows pump test without dumping water and is helpful when chlorinating water



Manifold kit with valves, drains and support hardware comes with system

Traffic guard supplied by plant engineer.