

Well Manager® Basic Control Package To Run Two Wells



**Collect entire well production
Or limit the amount withdrawn
and
Fill a pond, tank, cistern or tower
using our
Two Well Basic Control Package:**

- WM-2, Nema 1, UL Listed pump control panel to operate two well pumps using field adjustable timed cycles to get the most from each well. Runs one well at a time.
- Panel includes circuit breakers
- Push to test pump relays
- Each well pump has HOA switch
- Control panel available for ½ - 3 HP 120V or 240V submersible, jet or centrifugal pressure pumps. (*specify voltage ordering*)
- Run well and pressure pumps of any size using separate motor starters not included
- Door lights make trouble shooting a breeze
- Stored water level floats are pre-wired. Install in minutes
- Operate optional alarm for low stored water condition
- Over Fill Cut Off device turns well and pressure pump off if system overfills. Must be manually reset in this condition so owner knows there is a problem before damage occurs
- Ultra sensitive flow detector is immune to well grit, turns well pump off instantly if water fails to arrive at storage tank.
- Backflow preventer protects the aquifer from treatment chemical contamination

Electrical requirements for the two well controls: Two dedicated circuits. One 240volt, 60hz, 20amp and one 120 volt, 60hz, 15amp. If you plan to run a 240V pressure pump, we will install one additional 240V breaker in the control box at additional cost. (specify pump voltages when ordering).

Sold by:

Well Manager® is protected by US Patent 6077044; other US and Canadian Patents Pending
Made in USA by Reid Plumbing Products LLC, Hopewell, NJ
800-211-8070 outside the US +1 609-466-4347

<http://www.wellmanager.com>

**“The water you need and
the performance you want”**